

“ECOFLUID E”

Standard:

- G11
- G12
- G12+/G12++
- G12 evo
- G13
- G48
- G30
- G05
- Hybrid and Electric vehicles coolants (HEV - BEV - PHEV)
- HD coolants – Heavy Duty (tractors, agricultural vehicles, mining)
- Vintage cars coolants – Waterless antifreeze for vintage cars
- HP coolants – High performance waterless antifreeze for competitions and racing

AVAILABLE PACKAGING:

- BULK/ISOTANK/FLEXITANK
- IBC 1.000,00 KG
- BARREL 220,00 KG
- CAN 20KG/10KG

COLORING: customized

TECHNICAL DATA:

- MONOETHYLENE GLYCOL (MEG)
- CAS: 107-21-1
- EC: 203-473-3
- INDEX: 603-027-00-1
- REGISTRATION NUMBER: 01-2119456816-28

INHIBITION TECHNOLOGIES:

- IAT
- OAT
- SI-OAT
- HOAT
- Heavy Duty
- Low HOAT
- OAT low conductivity

APPLICATIONS:

AUTOMOTIVE, HEAVY TRACTION, AGRICULTURAL TRACTORS, ROAD TRACTORS, MINING, REFRIGERATION

NATIONAL, INTERNATIONAL AND MILITARY STANDARDS MET BY OUR ANTIFREEZE FORMULATIONS “ECOFLUID” (partial list):

- ASTM D 3306 - S.A.E. J 814
- ASTM D 4340 - S.A.E. J 1034
- ASTM D 4895
- ASTM D 8085
- ASTM D 15.22 “Non Aqueous Engine Coolant”
- CUNA NC 956 - 16
- B.S. 6580
- FW Heft R 443(D)
- FK Heft R 443(D)
- JIS K 2234 (j)
- UNE 26361-88 (E)
- Afnor R 15/601 (F)
- KSM 2142 (K)
- EMPA (CH)
- NATO S 759
- E/L 1415c (MIL Italy)

OEM SPECIFICATIONS MET BY OUR ANTIFREEZE FORMULATIONS “ECOFLUID” (partial list):

- FIAT 9.55523/41
- Porsche/VW/Audi/Seat/Skoda TL774C
- Mercedes-Benz DBL 7700
- MAN 324
- GM US 6277 M
- Volvo (Reg. n° 260)
- Ford WSS-M97b44-c
- Chrysler MS 9176
- BMW N 600 69.0
- Ford ESD M 97 B49-A
- Opel GM QL 13100
- DAF 74002
- Ford WSS-M97B44-D
- General Motors GM 6277M
- MAN MAN 324 SNF
- Mercedes-Benz MB 325.3
- Renault 41-01-001
- Renault Trucks
- SEAT TL 774 D & F
- Skoda TL 774 D & F
- Volkswagen VAG TL 774 D & F

- Volvo VCS
- Audi TL 774 G
- Bentley / Bugatti TL 774
- Cummins CES 14603
- Lamborghini TL 774 G
- Liebherr Min LH-01-COL3A
- MAN 324 Typ Si-OAT
- Mercedes-Benz MB 325.5 / 325.6
- Porsche
- Scania
- SEAT TL 774 G
- Skoda TL 774 G
- Volkswagen VAG TL 774 G
- Audi TL 774
- Bentley / Bugatti TL 774 J
- Lamborghini TL 774
- SEAT / Skoda TL 774 J
- Volkswagen VAG TL 774 J

BRAKE FLUIDS

Standard:

- DOT 3
- DOT 4
- DOT 5.1

AVAILABLE PACKAGING:

- BULK/ISOTANK/FLEXITANK
- IBC 1.000,00 KG
- BARREL 220,00 KG
- CAN 20 KG/10 KG

COLORING: specific

APPLICATIONS:

- HYDRAULIC BRAKE AND CLUTCH SYSTEMS IN VEHICLES
- HYDRAULIC BRAKING SYSTEM WITH ANTI-LOCK BRAKING SYSTEM (ABS) AND AUTOMATIC STABILITY CONTROL (ASC)
- BRAKING SYSTEMS FOR HEAVY-DUTY OR HEAVY-USE VEHICLES